继电器式多功能交流稳压器



TM series relay type multifunctional AC voltage stabilize



概述 General

TM系列继电器式多功能交流稳压器采用进口继电器控制,超宽范围的新型产品,具有延时,过压保护,市电、稳压自动转换等优良功能,挂壁式安装,能有效拓展和利用空间,流线外形,给人视觉以焕然一新之感,动作灵敏,定时准确,性能稳定,安全省电,造型美观,结构合理,使用方便,输入电压范围宽等优点,是电冰箱,电视机等高档家电良好的保护神。

TM series AC voltage stabilizer adopt relay switch-over to adjust the output voltage, possessing the protection against time-delay, over voltage and under voltage and the free switching between the electric supply and voltage stabilization, etc. It adopts the hanging type installation, which can effectively save and make use of the space, The soft overall color of streamline gives people a bright and new look. It offer the advantages of quick work, accurate timing, steady performance, safety and electricity-saving, excellent design, reasonable construction, easy operation, wide input voltage range, etc, The voltage stabilizers are the universal protectors in the high-grade household appliances, such as refrigerator, television, and so on.

适用范围

Application

照明系统,家用电器,空调设备,音箱设备。

Lighting equipment, household appliance, air-conditioner equipment, sound equipment

技术指标

Technical index

型号 Model	TM- 3000VA	TM- 5000VA	TM- 8000VA	TM- 10KVA
包装尺寸(cm) Package size	42×30 ×19.5	45×33 ×22	45×33 ×22	50×38.5 ×25
重量(Kg) Weight	12.5	18.5	21	25
输入电压 Input voltage	120~270V或140~260V			
输出电压 Output voltage	220±10%或220±8%			
频率 Frequency	50~60HZ			
过压保护 Over voltage Protection	245±5V			
环境温度 Ambient Temperature	-10°C ~+ 40°C			
温升 Temperature rise	<70k			
波形失真 Wave-form distortion	无附加波形失真 No additional wave-form distortion			
抗电强度 Dielectric Strength	1500V/2分钟			
使用方法 Operation Mode	可持续使用 Continuously operated			
绝缘电阻 Insulation resistance	> 2MΩ			